

GOVT. COLLEGE OF ENGINEERING AND RESEARCH, AWASARI

Awasari(Khurd) Tal: Ambegaon, Dist.Pune-412 405

Tel. No.02133-230582, E-Mail – gcoeara@gmail.com, Webesite : www.gcoeara.ac.in

No. GCOEARA/Store/2016-17/3707

Date: 10/11/2016

To,
HOD- Computer Engineering for display on College Website

Subject : Invitation for quotation for supply of Equipments (Civil Engineering- Strength of Material Lab)

Sealed quotations are invited from manufacturers / their authorised suppliers for supply of the following equipments/machinery to this institute. The quotation in specified format, along with necessary supporting documents should be sealed in an envelope and submitted to this office on or before the prescribed time and date mentioned this invitation letter.

Sr.No.	Name of the item with Specification	Qty.	Unit
1	Tile (Roofing and Flooring) Flexural Testing Machine	1	No
2	Abrasion Testing Machine for Flooring Tiles	1	No
	(Detail scope/specifications of supply will be as per enclosed sheet)		

Last date for submission of above quotations to this office is 22.11.2016 till 5.00 PM

Instructions to bidders and Terms & Conditons

- 1 The quotations must be submitted in sealed envelope, in prescribed format with details of enquiry number, laboratory name last date for submission etc. super scribed on envelope.
- 2 The quotations must be supported by necessary technical literature, and other documents.
- 3 The bidder must not be a defaulter to any Government authorities and must not have been black listed/debarred from supplying goods.
- 4 The bid must be for inclusive price of the goods, must include all taxes and levies, transportation charges, freight etc and for warranty of 2 years from the date of installation.
- 5 Rates quoted should be valid for 90 days from the last date of submission of offer.
- 6 The bid offer must comply with all technical specifications and requirements of the user department. Mere quoting lowest price will not be the criteria for award.
- 7 The bidder must mandatorily quote PAN number and VAT TIN, while submitting th quotation.
- 8 The consignee will make payment for the goods received by way of RTGS/NEFT/ECS, as the case may be. Hence the supplier will have to provide bank details to the consignee.
- 9 Payments will be done only after delivery, successful installation and working trial at the consignee's place. Advance payments will not be done.
- 10 This office reserves the right to reject any or all bid offers, without assigning any reason (/s), thereof.
- 11 List of documents to be attached - i) covering letter with details of bidders, address, telephone number, mobile number, email ID, name, signature and seal, ii) type of business entity-manufacturer / authorised dealer, any others (to be specified), iii) PAN card xerox, iv) sales tax / VAT TIN number v) offer letter stating make and model quoted, vi) authorization from manufacturer regarding support during bidding process and warranty period, in case the bidder is not a manufacturer, vii) technical literature of item quoted, viii) price quote along with taxation, inclusions and exclusions, if any, ix) undertaking that the bidder has not been black listed or debarred from supplying previously. x) undertaking about compaliance of terms and conditions mentioned in this quotation.

(Dr. A.S. Pant)
Principal

Govt.College of Engineering & Research Awasari
Awasari(khurd)

GOVERNMENT COLLEGE OF ENGINEERING AND RESEARCH AVASARI (KD)
DEPARTMENT OF CIVIL ENGINEERING

Sr. No.	Name of Equipments/Accessories/consumables with specifications	Quantity Required
	Strength of Material Lab	
1	<p>Tile (Roofing and Flooring) Flexural Testing Machine: Test rig should be as per IS: - 1237-1980 The equipment consist of two bearing rollers and a third self aligning loading roller, all 25 mm., in diameter. The center to center distance between bearing rollers can be set at 150, 200 or 250 mm., The loading is through double lever loading system by means of a steady flow of lead shot from a lead shot container to a receiver hung on the lever system. The rate of flow of lead shot is adjustable as per required rate of loading., The flow of lead shot stops automatically on failure of test specimen and the breaking load can be calculated by multiplying the weight of lead shot in the receiver by the lever ratio i.e. 12., Maximum capacity of the machine is 2 kN., Lever ratio is 1 : 12., Supplied complete with 20 kg lead shot.</p>	1
2	<p>Abrasion Testing machine for Flooring Tiles: Test rig shall be able to conducts test as per IS: 1237 and IS: 1706, It should consists of the following: - A grinding disc furnished with a replaceable grinding path and rotating horizontally about its vertical axis., A circular tray enclosing, holding device for test specimen., Reduction gear coupled to a motor for operation on 415 V, 50 Hz, 3 phase, AC Supply. Revolution counter. (Preset cumulative). A 7.5 Kg weight, abrasive powder and thickness gauge.</p>	1

Release

CDR S. B. (Civil)