

# GOVT. COLLEGE OF ENGINEERING AND RESEARCH, AWASARI

Awasari(Khurd) Tal: Ambegaon, Dist.Pune-412 405

Tel. No.02133-230582, E-Mail – gcoeara@gmail.com, Website : www.gcoeara.ac.in

No. GCOEARA/Store/2016-17/ 3784

Date: 10 NOV 2016

To,

As per addresses overleaf

*HOD, Comp. Engg. Dept For website display*

Subject : Invitation for quotation for supply of Equipments ( For Workshop Dept. )

Sealed quotations are invited from manufacturers / their authorised suppliers for supply of the following equipments/machinery to this institute. The quotation in specified format, along with necessary supporting documents should be sealed in an envelope and submitted to this office on or before the prescribed time and date mentioned this invitation letter.

| Sr.No. | Name of the item with Specification                    | Qty. | Unit |
|--------|--|------|------|
| 1      | Surface or Table Grinder Machine                       | 1    | 1    |
| 2      | 'C' Type power press (For sheet metal work)            | 1    | 1    |
| 3      | Double Body Fly press(For sheet metal work)            | 1    | 1    |
| 4      | Circle cutting machine (For sheet metal work)          | 1    | 1    |
|        | <b>Detail Scope of Supply is as per enclosed sheet</b> |      |      |

Last date for submission of above quotations to this office is 22.11.2016 till 5.00 PM

### Instructions to bidders and Terms & Conditions

- 1 The quotations must be submitted in sealed envelope, in prescribed format with details of enquiry number, laboratory name last date for submission etc. super scribed on envelope.
- 2 The quotations must be supported by necessary technical literature, and other documents.
- 3 The bidder must not be a defaulter to any Government authorities and must not have been black listed/debarred from supplying goods.
- 4 The bid must be for inclusive price of the goods, must include all taxes and levies, transportation charges, freight etc and for warranty of 2 years from the date of installation.
- 5 Rates quoted should be valid for 90 days from the last date of submission of offer.
- 6 The bid offer must comply with all technical specifications and requirements of the user department. Mere quoting lowest price will not be the criteria for award.
- 7 The bidder must mandatorily quote PAN number and VAT TIN, while submitting th quotation.
- 8 The consignee will make payment for the goods received by way of RTGS/NEFT/ECS, as the case may be. Hence the supplier will have to provide bank details to the consignee.
- 9 Payments will be done only after delivery, successful installation and working trial at the consignee's place. Advance payments will not be done.
- 10 This office reserves the right to reject any or all bid offers, without assigning any reason (/s), thereof.
- 11 List of documents to be attached - i) covering letter with details of bidders, address, telephone number, mobile number, email ID, name, signature and seal, ii ) type of business entity-manufacturer / authorised dealer, any others (to be specified), iii) PAN card xerox, iv) sales tax / VAT TIN number v) offer letter stating make and model quoted, vi) authorization from manufacturer regarding support during bidding process and warranty period, in case the bidder is not a manufacturer, vii) technical literature of item quoted, viii) price quote along with taxation, inclusions and exclusions, if any, ix) undertaking that the bidder has not been black listed or debarred from supplying previously. x) undertaking about compliance of terms and conditions mentioned in this quotation.

*(Signature)*  
(Dr. A.S. Pant )


Principal

Govt.College of Engineering & Research Awasari  
Awasari(khurd)




कर्मशाळा विभागात विविध सेक्शनमध्ये प्रात्यक्षिके शिकवण्याकरीता आवश्यक असणा-या मशीनरीची यादी खालील तक्त्यात गुणवर्णानुसार दर्शवण्यात आलेली आहे.

| अ.क्र.                             | मशीनचे नाव व गुणवर्णन   | नग                    |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
|------------------------------------|---|-----------------------|---|--------------------------|----|---------------------------|----|------------------------|----|------------------------|----|------------------|----|--------------------------------|---------|--------------------|----|-------------------------------|-----|--------------------|-----|-------------------------|----|------------------------------------|---|-----------------------|---|--------------------------|-----|---|
| १                                  | <p><b>Surface or Table Grinder Machine</b><br/> Maximum grinding length 750 mm.<br/> Maximum grinding width 250 mm.<br/> Distance centre of wheel , over table 125 mm ( Maximum ) Longitudinal travel speed 12 meters / minuts .Standard wheel size 250 mm. x 25 mm x 762 mm. Speed of wheel 2100 or 2625 rpm . Lubrication Centralised Automatic . Accessories Grinding wheel, wheel flange puller , wheel balancing mandrel, Table guards pump with fittings, machine lamp, Instruction manual. Permanent magnetic chuck , wheel balancing stand, coolant equipment magnetic separator, Demagnetiser, Universal machine vices, dust and exhaust equipment unit, wheel dressr over wheel head .</p>  | १                     |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| २                                  | <p><b>'C' Type power press<br/> (For sheet metal work)<br/> With Die Sets (5 Nos.) Installation &amp;<br/> Demonstration</b></p> <table border="1"> <tbody> <tr> <td>Capacity in Tons (mm)</td> <td>5</td> </tr> <tr> <td>Crankshaft Diameter (mm)</td> <td>70</td> </tr> <tr> <td>Adjustment of Stroke (mm)</td> <td>38</td> </tr> <tr> <td>Adjustment of Ram (mm)</td> <td>25</td> </tr> <tr> <td>Punch Hole in Ram (mm)</td> <td>25</td> </tr> <tr> <td>Hole in Bed (mm)</td> <td>63</td> </tr> <tr> <td>Bed Size (Length x Width) (mm)</td> <td>355x178</td> </tr> <tr> <td>Bed Thickness (mm)</td> <td>50</td> </tr> <tr> <td>Dist. between bed to Ram (mm)</td> <td>177</td> </tr> <tr> <td>Flywheel Dia. (mm)</td> <td>406</td> </tr> <tr> <td>Strokes per minute (mm)</td> <td>80</td> </tr> <tr> <td>H.P. Required For Geared(1440 RPM)</td> <td>1</td> </tr> <tr> <td>For Ungeared(960 RPM)</td> <td>1</td> </tr> <tr> <td>Floor To Top of Bed (mm)</td> <td>700</td> </tr> </tbody> </table> | Capacity in Tons (mm) | 5 | Crankshaft Diameter (mm) | 70 | Adjustment of Stroke (mm) | 38 | Adjustment of Ram (mm) | 25 | Punch Hole in Ram (mm) | 25 | Hole in Bed (mm) | 63 | Bed Size (Length x Width) (mm) | 355x178 | Bed Thickness (mm) | 50 | Dist. between bed to Ram (mm) | 177 | Flywheel Dia. (mm) | 406 | Strokes per minute (mm) | 80 | H.P. Required For Geared(1440 RPM) | 1 | For Ungeared(960 RPM) | 1 | Floor To Top of Bed (mm) | 700 | १ |
| Capacity in Tons (mm)              | 5   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Crankshaft Diameter (mm)           | 70  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Adjustment of Stroke (mm)          | 38  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Adjustment of Ram (mm)             | 25  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Punch Hole in Ram (mm)             | 25  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Hole in Bed (mm)                   | 63  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Bed Size (Length x Width) (mm)     | 355x178   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Bed Thickness (mm)                 | 50  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Dist. between bed to Ram (mm)      | 177   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Flywheel Dia. (mm)                 | 406   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Strokes per minute (mm)            | 80  |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| H.P. Required For Geared(1440 RPM) | 1   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| For Ungeared(960 RPM)              | 1   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |
| Floor To Top of Bed (mm)           | 700   |                       |   |                          |    |                           |    |                        |    |                        |    |                  |    |                                |         |                    |    |                               |     |                    |     |                         |    |                                    |   |                       |   |                          |     |   |

  
Workshop Superintendent  
Govt. College of Engg. & Research.  
Avasari Khurd, Dist. Pune.



| अ.क्र.                   | मशीनचे नाव व गुणवर्णन   | नग            |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
|--------------------------|---|---------------|-------------------|---------------------|--------------|-------------------|----|--------------------------|---------------|-----------------------|----|----------------|-----|-----------------------|-----|-------------------------|------|--------------------|----|---|
| ३                        | <b>Double Body Fly press</b><br><b>(For sheet metal work)</b><br><b>With Die Sets, (5 Nos.) Installation</b><br><b>&amp; Demonstration</b> <table border="1" style="margin-left: 20px;"> <tr> <td>Base to Guide</td> <td>190</td> </tr> <tr> <td>Centre to back</td> <td>-</td> </tr> <tr> <td>Diameter of Screw</td> <td>48</td> </tr> <tr> <td>Hole in Bed Without Ring</td> <td>76</td> </tr> <tr> <td>Hole in Bed with Ring</td> <td>38</td> </tr> <tr> <td>Between Frames</td> <td>152</td> </tr> <tr> <td>Diameter of Fly Wheel</td> <td>670</td> </tr> <tr> <td>Hole in Ram ( Diameter)</td> <td>25.4</td> </tr> <tr> <td>Hole in Ram (Deep)</td> <td>38</td> </tr> </table> | Base to Guide | 190               | Centre to back      | -            | Diameter of Screw | 48 | Hole in Bed Without Ring | 76            | Hole in Bed with Ring | 38 | Between Frames | 152 | Diameter of Fly Wheel | 670 | Hole in Ram ( Diameter) | 25.4 | Hole in Ram (Deep) | 38 | १ |
| Base to Guide            | 190   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Centre to back           | -   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Diameter of Screw        | 48  |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Hole in Bed Without Ring | 76  |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Hole in Bed with Ring    | 38  |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Between Frames           | 152   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Diameter of Fly Wheel    | 670   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Hole in Ram ( Diameter)  | 25.4  |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Hole in Ram (Deep)       | 38  |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| ४                        | <b>Circle cutting machine</b><br><b>Hand Operated / Motorised Operated</b> <table border="1" style="margin-left: 20px;"> <tr> <td>Size</td> <td>15", 18", 24", 36</td> </tr> <tr> <td>Cap.Cuts Circle Dia</td> <td>76mm to 900m</td> </tr> <tr> <td>Cuts</td> <td></td> </tr> <tr> <td>Thickness M.S</td> <td>0.90 to 1.5mm</td> </tr> </table>   | Size          | 15", 18", 24", 36 | Cap.Cuts Circle Dia | 76mm to 900m | Cuts              |    | Thickness M.S            | 0.90 to 1.5mm | १                     |    |                |     |                       |     |                         |      |                    |    |   |
| Size                     | 15", 18", 24", 36   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Cap.Cuts Circle Dia      | 76mm to 900m  |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Cuts                     |   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |
| Thickness M.S            | 0.90 to 1.5mm   |               |                   |                     |              |                   |    |                          |               |                       |    |                |     |                       |     |                         |      |                    |    |   |

  
 10/11/16  
 Workshop Superintendent  
 Govt. College of Engg. & Research,  
 Avasari Khurd, Dist. Pune.